




TEBAOFLEX CABLE

DATA SHEET

Mining&Industrial cable

TYPE SHD-GC 3/C 2000 V CPE CABLE

Heavy-duty portable mining power cable



APPLICATION

For heavy-duty portable power circuits not exceeding 2,000 volts, including longwall shearers, continuous miners, loaders, drills, conveyors, pumps and mobile equipment.

CONSTRUCTION

Parameter	Value
Conductor	Flexible tinned copper
Insulation	90 deg C ethylene-propylene rubber (EPR)
Shielding	Tinned copper and color-coded nylon braid
Ground wires	Flexible tinned copper
Ground check	Flexible tinned copper with yellow polypropylene insulation
Jacket	Reinforced mold-cured thermosetting chlorinated polyethylene (CPE) jacket

CABLE CHARACTERISTICS

Parameter	Value
Design standard	ICEA S-75-381 / NEMA WC-58
Rated voltage	2000 V
Maximum conductor temperature	90 deg C continuous
Cable construction	Three power conductors, grounding conductors and a ground check conductor with metallic shielding

TECHNICAL DATA

Complete nominal dimensional data. Source ordering codes have been omitted.

POWER CONDUCTOR AND CABLE DIMENSIONS							
Power conductor AWG/kcmil	Area AWG/kcmil mm2	Nearest standard metric mm2	No. of wires per conductor	Insulation thickness mils	Jacket thickness mils	Nominal outside dimensions in.	Approx. weight lbs/1000 ft
6	0.35	0.50	133	70	155	1.29	1160
4	0.52	0.50	259	70	155	1.40	1490
2	0.82	1.00	259	70	170	1.59	2000
1	1.31	1.50	259	80	190	1.76	2450
1/0	2.08	2.50	266	80	190	1.86	2840
2/0	3.31	4	323	80	205	2.00	3400
3/0	5.26	6	418	80	205	2.13	3680
4/0	8.37	10	532	80	220	2.31	4860
250	13.30	16	627	95	220	2.51	5950
350	21.15	25	888	95	235	2.81	7400
500	33.62	35	1221	95	265	3.19	10100

GROUND CHECK CONDUCTOR		
Ground check AWG	Area mm2	No. of wires per conductor
10	0.35	49
8	0.52	133
6	0.82	133
5	1.31	133
4	2.08	259
3	3.31	259
2	5.26	259
1	8.37	259
1/0	13.30	266
2/0	21.15	323
4/0	33.62	532

TECHNICAL DATA

Complete nominal dimensional data. Source ordering codes have been omitted.

AMPACITY	
Power conductor AWG/kcmil	Ampacity at 40 deg C ambient, A
6	93
4	122
2	159
1	184
1/0	211
2/0	243
3/0	279
4/0	321
250	355
350	435
500	536

NOTES

Nominal values are for cable selection. Actual cable dimensions may vary due to manufacturing tolerances.

CERTIFICATIONS

